



Valves and Fittings Supplies

**1" - 4"**  
**2-pc Flange Ball Valve, Full Bore,**  
**ANSI/TE/TD, with ISO 5211G**

**SP2PDMANSI/TE/TD**


**FIRE SAFE APPROVED**

- I Approval no. 285692, Fire Safe Standard API 607
- I Investment Casting Body and Cap
- I Flange Ends: ASME B16.5
- I Face To Face: ANSI 16.10
- I Pressure Rating: ANSI/TE/TD Class 150
- I Material: CF8M,CF8,CF3M,WCB
- I Mounting Pad: ISO 5211



**MATERIAL LIST**

ITEM	PART	MATERIAL	QTY
1	BODY	CF8M	1
2	CAP	CF8M	1
3	BALL	SS316	1
4	BALL SEAT	PTFE	2
5	STEM	SS316	1
6	THRUST WASHER	PTFE	1
7	O-RING	VITON	1
8	STEM PACKING	PTFE	2
9	GLANDE	SS304	1
10	WASHER	SS304	2
11	NUT	SS304	2
12	WASHER	SS304	1
13	STOP PIN	SS304	1
14	HANDLE	SS304	1
15	HANDLE COVER	PLASTIC	1
16	LOCK	SS304	1
17	BODY GASKET	PTFE	1
18	BOLT	SS304	(4)(6)(8)



**DIMENSION TABLE**

SIZE	D	L	T	F	D1	D2	D3	N-D1	H1	H	W	aP	ISO5211	NM	KGS
1"	25	127	11	1.6	108	79	51	4-16	59	95	160	11	F04/F05	12	2.82
1-1/4"	32	140	13	1.6	117	89	64	4-16	71	108	160	11	F04/F05	17	3.89
1-1/2"	38	165	15	2	125	98	73	4-16	76	114	185	14	F05/F07	30	5.05
2"	50	178	16	2	150	121	92	4-19	85	124	185	14	F05/F07	48	7.15
2-1/2"	65	190	17	2	180	140	105	4-19	102	148	230	17	F07/F10	58	13.91
3"	76	203	20	2	190	152	127	4-19	112	158	230	17	F07/F10	96	15.90
4"	94	229	24	2	230	191	157	4-19	141	191	230	17	F07/F10	124	26.40